

Jackup Rig Brakes

82,000 SERIES FOR
OIL & GAS PLATFORMS

SAFETY FIRST: SECURE JACKUP RIG FOUNDATIONS

Jackup rigs rely on precision engineering and strict regulations to ensure the safety of workers, equipment and revenue. Stearns 82,000 Series solenoid actuated (SAB) brakes are designed to meet the demands of jackup rigs, delivering safe, reliable and long-lasting solutions to both commercial and domestic customers.

82,000 SERIES BENEFITS

- Zinc-rich factory primer reduces housing oxidation in the harshest climates
- 115VAC 50W space heater combats condensation build up to prolong brake life
- Strategically engineered gaskets prevent water seepage into brake
- Brake position indicator allows safe observation when brake is set or released
- Manufactured & assembled in the US for fast & affordable shipping
- US-based technical & service support by dedicated brake experts

MODIFICATION OPTIONS

- Mechanical status, proximity status & thermal switch options
- Conduit box with terminal strip or internally mounted terminal strip
- Horizontal & vertical mounting configurations
- Aluminum or cast iron housing
- Bore & keyway size
- Internal encoder

STEARNS™

Regal Rexnord

Contact us: 414-272-1100

stearnsbrakes.com | regalrexnord.com

The proper selection and application of products and components, including assuring that the product is safe for its intended use, are the responsibility of the customer. To view our Application Considerations, please visit <https://www.regalrexnord.com/Application-Considerations>.

To view our Standard Terms and Conditions of Sale, please visit <https://www.regalrexnord.com/Terms-and-Conditions-of-Sale>.

"Regal Rexnord" is not indicative of legal entity. Refer to product purchase documentation for the applicable legal entity. Regal Rexnord and Stearns are trademarks of Regal Rexnord Corporation or one of its affiliated companies.

© 2024, 2025 Regal Rexnord Corporation, All Rights Reserved. MCF-10953-STEN-US 03/25



FEATURES

- Torque: Max. 440 lb-ft
- Cast or Ductile Iron Enclosure
- Self-Adjusting Design
- Deadman Side Release
- 2" NPT Plug in Housing
- Brass Pressure Plates & Stationary Discs
- Stainless Steel Splined Hub
- Class 180(H) Coil Insulation
- IP 56 Rating
- ABS & cURus Certified
- AC Voltage

