UPGRADE YOUR 82,000 series



Stearns customizable brakes have long been a critical element in a vast variety of industrial applications proven to deliver sustainability and safety. That is why motor manufacturers trust our brakes to stop and/or hold loads.

AVAILABILITY ON HAND & READY TO SHIP



More Features

Retain	While adding the following key features:
Self-Adjusting Design	Corrosion resistant treatment
Certified: CSA File LR	Improved IP rating (IP56 vs IP54 standard)
Cast Iron Enclosure	Deadman side release vs maintained standard pull release
Spring-Set Power	115VAC 50W Space Heater
Manual Release	Brake position indicator to indicate when the brake is released or set

WHY CHOOSE STEARNS?

- ABS, CSA Certified
- IP56 Enclosure Rating
- Cast Iron Enclosure
- Spring-Set, Power Released

Our heavy-duty 82,000 series brakes are ideal for demanding applications like offshore drilling.

Fastened to an operations' legs, our brakes lock the legs in place after they are lowered to the ocean floor so that a foundation is firmly established to support the hull, and secure the crew and equipment safely.

CONTACT US

www.stearnsbrakes.com 5150 S. International Drive Cudahy, WI 53110 Tel: **1-414-272-1100**



About the 1-082-042 SERIES - In Stock

Shown: 82,000 series support plate with green zinc primer, space heater, mechanical & proximity status switches, encapsulated coil, fiberglass protective leadwire sleeving and undercover release.

Dimensional information and specifications listed in Stearns Catalog as the 82,000 series.

STANDARD 1-082-042 SERIES FEATURES INCLUDE:

CORROSION CONTROL FEATURES

Space heater - 115 volts

Stainless wear adjust mechanism

Stainless external hardware

Corrosion resistance treatment

Zinc primer support plate surfaces

MATERIAL FEATURES

Brass pressure plates and stationary discs

Stainless steel splined brake hub

Stainless nameplates

ELECTRICAL FEATURES

Class H insulation

IN STOCK BRAKES ARE BUILT WITH The following features:

Torque: 330 ft-lb**

2" NPT plug in housing

Side release (pull release is standard)

Deadman side release

Solenoid actuated warning switch

O-ring gasket housing to endplate

O-ring gasket to mount surface

**Please note the torque can be adjusted up to 440 ft-lb

MODIFICATION OPTIONS INCLUDE:

01 Torque

02 Coil voltage

03 Bore & keyway size

04 Switch options

05 Conduit box with terminal strip

CONTACT US

www.stearnsbrakes.com 5150 S. International Drive Cudahy, WI 53110 Tel: **1-414-272-1100**